




| RGB  
15156



Technical data	
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Optic	Diffused
Power	6 W
Current intensity	500mA
CCT / Tonalità	RGB
C.C. / C.V.	CC
Safety class	3
IP	IP65
IK	10
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	No
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing diffuser	
Material	PE
Colour	neutral

Finishing mounting frame	
Material	PE
Colour	white

Electronics	
	N/O button - IR Remote - art.



| RGB  
**15156**





Double emission floor lamp for outdoor application. The RGB LED light source with a diffused light distribution is composed of 1 powerleds LEDs.

The diffuser is made of pe; the mounting frame is made of pe, with a white finish. The ingress protection degree is IP65; the total weight is of 1.440 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 6 W.

The device features protection class III and can be floor-mounted with an outer casing, code 14930(for concrete or masonry).

Oh!\_FL65 | Floor Lamp | Accessories  
15156

		Outer casing - outer casing for installation on ground or on concrete	<div>Code</div> <div>14930</div>
		Pegs	<div>Code</div> <div>14931</div>