

Floor Lamp | 1 x powerLEDs 6 W 500 mA | RGB 15161














/	
	ø38

Technical data	
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Optic	Diffused
Power	6 W
Current intensity	500mA
CCT / Tonalità	RGB
C.C. / C.V.	CC
Safety class	3
IP .	IP65
IK	10
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	No
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing diffuser	
Material	PE
Colour	neutral

Finishing mounting frame			
Material	PE		
Colour	white		

Electronics



N/O button - IR Remote

Oh!_FL65



Floor Lamp | 1 x powerLEDs 6 W 500 mA | RGB 15161

Double emission floor lamp for outdoor application. The RGB LED light source with a diffused light distribution is composed of 1 powerleds LEDs.

The diffuser is made of pe; the mounting frame is made of pe, with a white finish. The ingress protection degree is IP65; the total weight is of 2.600 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 6 W.

The device features protection class III and can be floor-mounted with an outer casing, code 14930(for concrete or masonry).

Oh!_FL65



Oh!_FL65 | Floor Lamp | Accessories **15161**

The state of the s	22 Ø 11	Outer casing - outer casing for installation on ground or on concrete	Code 14930
	30 J	Pegs	Code 14931
	0 30	anti-theft - anti-theft ground fixing bracket	Code <u>14080</u>