


Floor Lamp | 1 x powerLEDs 12 W 500 mA | RGB 15163








Technical data	
nstallation position	Floor
nstallation environment	Outdoor
ight Source	LED
Optic	Diffused
Power	12 W
current intensity	500mA
CT / Tonalità	RGB
c.C. / C.V.	CC
afety class	3
	IP65
	10
low wire test	650°
irect mounting on normally flammable surfaces	Yes
Ξ	Yes
ΓL	No
river included	No
duzione	No
mergency mode	No
otion sensor	No
rectional	No
Iting	No
alk-over	No
ive-over	No
able included	No
esin potting	No

Finishing diffuser				
Material	PE			
Colour	neutral			

Finishing mounting frame				
Material	PE			
Colour	white			

Electronics



Oh!_FL65



Floor Lamp | 1 x powerLEDs 12 W 500 mA | RGB **15163**

Double emission floor lamp for outdoor application. The RGB LED light source with a diffused light distribution is composed of 1 powerleds LEDs.

The diffuser is made of pe; the mounting frame is made of pe, with a white finish. The ingress protection degree is IP65; the total weight is of 4.700 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 12 W.

The device features protection class III and can be floor-mounted with an outer casing, code 14930(for concrete or masonry).

Oh!_FL65



Oh!_FL65 | Floor Lamp | Accessories 15163

	22	Outer casing - outer casing for installation on ground or on concrete	Code 14930
	0 13	Pegs	Code 14931
7111\$000	0 34	anti-theft - anti-theft ground fixing bracket	Code 14081