




Pendant Luminaires | 220-240 V | 1xE14
2644



| Technical data | |
|--|-----------------|
| Collection | linealight |
| Installation position | Ceiling |
| Installation environment | Indoor |
| Lamp cap | 1 x E14 Max 30W |
| Frequency | 50-60 Hz |
| Optic | Diffused |
| Light emission direction | downward |
| Safety class | 1 |
| IP | IP20 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Induzione | No |
| Emergency mode | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |

| Finishing casing | |
|------------------|------------------|
| Material | Ceramic |
| Colour | brown decoration |
| Processing | Coating |

| Finishing diffuser | |
|--------------------|--------------|
| Material | Glass |
| Colour | white |
| Processing | Sandblasting |

| Finishing mounting frame | |
|--------------------------|---------|
| Material | Iron |
| Colour | rust |
| Processing | Coating |



Pendant Luminaires | 220-240 V | 1xE14
2644

Double emission pendant luminaires for indoor application. Compatibility:
LED lamp, compact fluo 8 W, halogen 30 W; lamp cap 1xE14.

The device body is made of ceramic and features a brown decoration finish, processed by means of coating; the diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a rust finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 0.960 kg.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features

| | |
|------------------------|--------|
| Luminous flux (source) | 430 lm |
| Colour temperature | 2500 K |
| Colour rendering index | 100 Ra |