Campana_P

Pendant Luminaires | 220-240 V | 1xE27 4431



| | T |
|------------|---|
| max 130 | |
| | |

ٹ ليے الحو (ا

ø25

Finishing casing

| Technical data | |
|--|-----------------|
| Collection | linealight |
| Installation position | Ceiling |
| Installation environment | Indoor |
| Lamp cap | 1 x E27 Max 57W |
| Frequency | 50-60 Hz |
| Optic | Diffused |
| Light emission direction | downward |
| Safety class | 1 |
| IP | IP20 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Induzione | No |
| Emergency mode | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |

| Material | Iron |
|------------------|----------------|
| Colour | nickel |
| Processing | Electroplating |
| Finishing diffus | er |
| Material | Glass |
| Colour | white |
| Processing | Sandblasting |
| Finishing moun | ting frame |
| Material | Iron |
| Colour | nickel |
| Processing | Electroplating |

Pendant Luminaires | 220-240 V | 1xE27 4431

Single emission pendant luminaires for indoor application. Compatibility: LED lamp, compact fluo 20 W, halogen 57 W; lamp cap 1xE27.

The device body is made of iron and features a nickel finish, processed by means of electroplating; the diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a nickel finish, processed by means of electroplating. The ingress protection degree is IP20; the total weight is of 1.740 kg.

The device features protection class I and can be ceiling-mounted.

| Illuminotechnical Features | | |
|----------------------------|---------|--|
| Luminous flux (source) | 1300 lm | |
| Colour temperature | 2500 K | |
| Colour rendering index | 100 Ra | |