


Pendant Luminaires | 220-240 V | 3xG9
4649



| Technical data | |
|--|------------|
| Collection | linealight |
| Installation position | Ceiling |
| Installation environment | Indoor |
| Power | 3 x 48 |
| Lamp cap | 3 x G9 |
| Frequency | 50-60 Hz |
| Optic | Diffused |
| Light emission direction | downward |
| Safety class | 1 |
| IP | IP20 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Induzione | No |
| Emergency mode | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |

| Finishing casing | |
|------------------|----------------|
| Material | Iron |
| Colour | chrome |
| Processing | Electroplating |

| Finishing diffuser | |
|--------------------|-------------|
| Material | Glass |
| Colour | transparent |

| Finishing mounting frame | |
|--------------------------|----------------|
| Material | Iron |
| Colour | chrome |
| Processing | Electroplating |



Pendant Luminaires | 220-240 V | 3xG9
4649

Double emission pendant luminaires for indoor application. Halogen lamp included 48W, lamp cap 3xG9.

The device body is made of iron and features a chrome finish, processed by means of electroplating; the diffuser is made of glass; the mounting frame is made of iron, with a chrome finish, processed by means of electroplating. The ingress protection degree is IP20; the total weight is of 7.180 kg.

The device features protection class I and can be ceiling-mounted.

| Illuminotechnical Features | |
|----------------------------|---------|
| Luminous flux (source) | 2220 lm |
| Colour temperature | 2800 K |
| Colour rendering index | 100 Ra |