




Ceiling Lights | 220-240 V | 1xG9  
4650



Technical data	
Collection	linealight
Installation position	Wall lights - Ceiling
Installation environment	Indoor
Power	1 x 48
Lamp cap	1 x G9
Frequency	50-60 Hz
Optic	Diffused
Light emission direction	downward
Safety class	1
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing diffuser	
Material	Glass
Colour	transparent

Finishing mounting frame	
Material	Iron
Colour	chrome
Processing	Electroplating



Ceiling Lights | 220-240 V | 1xG9  
**4650**

Double emission ceiling lights for indoor application. Halogen lamp included 48W, lamp cap 1xG9.

The diffuser is made of glass; the mounting frame is made of iron, with a chrome finish, processed by means of electroplating. The ingress protection degree is IP20; the total weight is of 1.900 kg.

The device features protection class I and can be wall lights or ceiling-mounted.

Illuminotechnical Features	
Luminous flux (source)	740 lm
Colour temperature	2800 K
Colour rendering index	100 Ra