




Uplights | 220-240 V | 1xGU10
52951



Technical data	
Installation position	Floor
Installation environment	Outdoor
Lamp cap	1 x GU10 Max
Optic	Diffused
Safety class	1
IP	IP67
IK	09
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Emergency mode	No
Directional	Yes
Tilting	No
Walk-over	No
Drive-over	3000 Kg
Cable included	No
Resin potting	No

Finishing casing

Material	Aluminium
Colour	black
Processing	Coating

Finishing diffuser

Material	Glass
Colour	transparent

Finishing mounting frame

Material	Stainless steel 316
Processing	Shot peening



Uplights | 220-240 V | 1xGU10
52951

Single emission uplights for outdoor application. Compatibility:, halogen 35 W; lamp cap 1xGU10.

The device body is made of aluminium and features a black finish, processed by means of coating; the diffuser is made of glass; the mounting frame is made of stainless steel, processed by means of shot peening. The ingress protection degree is IP67; the total weight is of 0.672 kg.

The device features protection class I and can be floor-mounted with an outer casing, code 52700(for concrete or masonry).

Illuminotechnical Features

Luminous flux (source)	230 lm
Colour temperature	2700 K
Colour rendering index	100 Ra



Outer casing
L=122mm, H=180mm, D=122mm

Code
52700



Cable gland - Terminal with IP68 cable glands for joints and connections.

Code
E41017



Cable junction - Kit Watertight junction with resin

Code
E41025