## Ceiling Lights | 220-240 V | 1xGU10 59404



Technical data		
Installation position	Ceiling	
Installation environment	Indoor	
Lamp cap	1 x GU10 Max	
Optic	Diffused	
Safety class	2	
IP	IP40	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
ETL	No	
Emergency mode	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	

Finishing casing			
Material	Aluminium		
Colour	White RAL 9003		
Processing	Coating		
Finishing mounting frame			
Material	Aluminium		
Colour	White RAL 9003		
Processing	Coating		

## Ceiling Lights | 220-240 V | 1xGU10 59404

Single emission ceiling lights for indoor application. Compatibility:, halogen 35 W; lamp cap 1xGU10.

The device body is made of aluminium and features a white ral 9003 finish, processed by means of coating; the mounting frame is made of aluminium, with a white ral 9003 finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 0.51 kg.

The device features protection class II and can be ceiling-mounted.

Illuminotechnical Features	
Luminous flux (source)	230 lm
Colour temperature	2700 K
Colour rendering index	100 Ra