





Wall Lights | 1 x powerLED 2,0 W 350 mA | CRI 80
60920N07







140 x
80



Technical data	
Installation position	Wall lights - Wall lights - Ceiling - Ceiling
Installation environment	Indoor
Light Source	LED
Optic	Asymmetric
Power	2 W
Luminous flux (source)	140 lm
Current intensity	350mA
CCT / Tonalità	4000 K
Colour rendering index	80 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Operating temperature	-40°C / +100°C
Driver included	No
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing	
Material	plaster
Colour	white

Finishing diffuser	
Material	PMMA
Colour	transparent

Electronics	
	On/Off Driver 1 art.
	On/Off Driver 2 art.
	DALI - Push and Simply Dim 1 art.
	1-10V - N/O button 1 art.

Wall Lights | 1 x powerLED 2,0 W 350 mA | CRI 80
60920N07

Single emission wall lights for indoor application. The natural white LED light source with a diffused light distribution is composed of 1 powered LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 140 lm, with a 70.0 lm/W nominal luminous efficacy.



The device body is made of plaster and features a white finish; the diffuser is made of pmma. The ingress protection degree is IP20; the total weight is of 0.38 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 2,0 W.

The device features protection class III and can be wall lights, wall lights, ceiling or ceiling-mounted, with a 140 x 140 mm hole (in plasterboard) with an outer casing, code 61270(for concrete or masonry).

Illuminotechnical Features	
Luminous flux (source)	140 lm
Colour temperature	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	80 Ra

Gypsum_Wf1 | Wall Lights | Accessories
60920N07



Outer casing - formwork for concrete
L=140mm, H=172mm, D=51mm

Finish	Code
Grey	61270



Thick - KIT thicknesses for installation on plasterboard

Code
60830