


D-Retta_1



Bollard & Pole | 220-240 V | stripLED 5 W 24 V | CRI 80
64120W00



Technical data	
Designer	Studio RIGO
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Optic	Diffused
Power	5 W
Luminous flux (source)	320 lm
Frequency	50 - 60 - Hz
CCT / Tonalità	3000 K
Colour rendering index	80 Ra
AC / DC	AC-DC
Safety class	2
IP	IP65
IK	05
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing	
Material	Wood
Colour	teak

Finishing diffuser	
Material	PMMA
Colour	sandblasted

Bollard & Pole | 220-240 V | stripLED 5 W 24 V | CRI 80
64120W00

Single emission bollard & pole for outdoor application. The warm white LED light source with a diffused light distribution is composed of 24 stripLEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 320 lm, with a 64.0 lm/W nominal luminous efficacy.

The device body is made of wood and features a teak finish; the diffuser is made of pmma. The ingress protection degree is IP65; the total weight is of 1.54 kg. The power supply driver is included in the delivery.

The total absorbed power is 5 W.

The device features protection class II and can be floor-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	28 %
Luminous flux (source)	320 lm
Luminaire luminous flux	90 lm
Consumption	5 W
Luminaire efficacy	18 lm/W
Colour temperature	3000 K
Colour rendering index	80 Ra

UGR	
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20
UGR transversal	< 19
UGR axial	< 19

