





Wall Lights | 100-240 V | 1 x powerLED 2,0 W 500 mA | CRI 80  
64563W60



| Technical data                                 |               |
|--|---------------|
| Installation position                          | Wall lights   |
| Installation environment                       | Outdoor       |
| Light Source                                   | LED           |
| Optic  | 60°           |
| Power  | 2 W           |
| Luminous flux (source)                         | 144 lm        |
| Frequency                                      | 50 - 60 Hz    |
| CCT / Tonalità                                 | 3000 K        |
| Colour rendering index                         | 80 Ra         |
| AC / DC  | DC            |
| Safety class                                   | 2             |
| IP   | IP65          |
| Glow wire test                                 | 850°          |
| Direct mounting on normally flammable surfaces | Yes           |
| CE   | Yes           |
| ETL  | No            |
| Operating temperature                          | -20°C / +50°C |
| Driver included                                | Yes           |
| Induzione                                      | No            |
| Emergency mode                                 | No            |
| Directional                                    | No            |
| Tilting  | No            |
| Walk-over                                      | No            |
| Drive-over                                     | No            |
| Cable included                                 | No            |
| Resin potting                                  | No            |

| Finishing casing |         |
|------------------|---------|
| Material         | Beton   |
| Colour           | neutral |

Wall Lights | 100-240 V | 1 x powerLED 2,0 W 500 mA | CRI 80  
**64563W60**

Single emission wall lights for outdoor application. The warm white LED light source with a 60° light distribution is composed of 1 powered LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 144 lm, with a 72.0 lm/W nominal luminous efficacy.

The device body is made of beton and features a neutral finish. The ingress protection degree is IP65; The power supply driver is included in the delivery.

The total absorbed power is 2,0 W.

The device features protection class II and can be wall lights-mounted.

| Illuminotechnical Features |         |
|----------------------------|---------|
| Light Output Ratio (LOR)   | 50 %    |
| Luminous flux (source)     | 144 lm  |
| Luminaire luminous flux    | 73 lm   |
| Consumption                | 2,5 W   |
| Luminaire efficacy         | 29 lm/W |
| Colour temperature         | 3000 K  |
| Colour rendering index     | 80 Ra   |

| UGR               |          |
|-------------------|----------|
| X=4H   Y=8H       | S=0.25H  |
| Reflection factor | 70/50/20 |
| UGR transversal   | < 19     |
| UGR axial         | > 25     |

