








Pendant Luminaires | topLED 70 W 24 V | CRI 80
64585W00



Technical data	
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optic	Diffused
Light emission direction	upward
Power	70 W
Luminous flux (source)	9355 lm
Tensione	24V
CCT / Tonaltà	3000 K
Colour rendering index	80 Ra
C.C. / C.V.	CV
Safety class	3
IP	IP40
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Operating temperature	-40°C / +85°C
Driver included	No
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing	
Material	Aluminium
Colour	embossed white RAL 9003
Processing	Coating

Electronics	
	N/O button
	DALI - 1-10V
	Switching Driver

Pendant Luminaires | topLED 70 W 24 V | CRI 80
64585W00


Single emission pendant luminaires for indoor application. The warm white LED light source with a diffused light distribution is composed of 336 topLED LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 9355 lm, with a 133.6 lm/W nominal luminous efficacy.

The device body is made of aluminium and features an embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP40; the total weight is 6 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 70 W.


The device features protection class III and can be ceiling-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	42 %
Luminous flux (source)	9355 lm
Luminaire luminous flux	4016.68 lm
Consumption	51 W
Luminaire efficacy	78 lm/W
Colour temperature	3000 K
Colour rendering index	80 Ra



3.0	11.78	E(180°) E(C0)	117.0°	130 6
2.5	9.81	E(180°) E(C0)	117.0°	187 9
2.0	7.85	E(180°) E(C0)	117.0°	293 14
1.5	5.89	E(180°) E(C0)	117.0°	521 25
1.0	3.93	E(180°) E(C0)	117.0°	1171 55
0.5	1.96	E(180°) E(C0)	117.0°	4685 221


Abstand [m] Cone diameter [m] Illuminance [lx]
 C0 - C180 (Hal beam angle: 126.0°)



Suspensions

Code


64575



Fixing base

Code

64578



Fixing base

Code

64586