







Pendant Luminaires | topLED 37 W 24 V | CRI 80
64682W00



Technical data	
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optic	Diffused
Light emission direction	upward
Power	37 W
Luminous flux (source)	4678 lm
Tensione	24V
CCT / Tonalità	3000 K
Colour rendering index	80 Ra
C.C. / C.V.	CV
Safety class	3
IP	IP40
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Operating temperature	-40°C / +85°C
Driver included	No
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing	
Material	Aluminium
Colour	black RAL 9005
Processing	Coating

Electronics	
	Switching Driver
	N/O button
	DALI - 1-10V



Pendant Luminaires | topLED 37 W 24 V | CRI 80
64682W00


Single emission pendant luminaires for indoor application. The warm white LED light source with a diffused light distribution is composed of 168 topLEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 4678 lm, with a 126.4 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a black ral 9005 finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 2.6 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 37 W.


The device features protection class III and can be ceiling-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	42 %
Luminous flux (source)	4678 lm
Luminaire luminous flux	2010.84 lm
Consumption	27 W
Luminaire efficacy	75 lm/W
Colour temperature	3000 K
Colour rendering index	80 Ra



3.0	11.78	E(180°) E(C0)	117.0°	65 3
2.5	9.81	E(180°) E(C0)	117.0°	94 4
2.0	7.85	E(180°) E(C0)	117.0°	147 7
1.5	5.89	E(180°) E(C0)	117.0°	261 12
1.0	3.93	E(180°) E(C0)	117.0°	586 28
0.5	1.96	E(180°) E(C0)	117.0°	2345 111


Abstand [m] Cone diameter [m] Illuminance [lx]
 C0 - C180 (Hal beam angle: 126.0°)



Fixing base

Code


64674



Fixing base

Code

64678



Suspensions

Code

64670