



Wall Lights | 220-240 V | 1xE14
71640





Technical data	
Collection	linealight
Installation position	Wall lights - Ceiling
Installation environment	Indoor
Lamp cap	1 x E14 Max 46W
Frequency	50-60 Hz
Optic	Diffused
Light emission direction	frontal
Safety class	1
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing diffuser	
Material	Glass
Colour	white
Processing	Silk-screening

Finishing mounting frame	
Material	Iron
Processing	Coating

Wall Lights | 220-240 V | 1xE14
71640

Double emission wall lights for indoor application. Compatibility: LED lamp, compact fluo 8 W, halogen 46 W; lamp cap 1xE14.

The diffuser is made of glass with a silk-screening treatment; the mounting frame is made of iron, processed by means of coating. The ingress protection degree is IP20; the total weight is of 0.605 kg.

The device features protection class I and can be wall lights or ceiling-mounted.

Illuminotechnical Features	
Luminous flux (source)	430 lm
Colour temperature	2500 K
Colour rendering index	100 Ra