




Ceiling Lights | 220-240 V | topLED 33 W 700 mA | CRI 90
7653



| Technical data | |
|--|---------------------|
| Collection | ma[&]de |
| Installation position | Ceiling |
| Installation environment | Indoor |
| Light Source | LED |
| Circuit structure | topLED |
| Optic | Diffused |
| Light emission direction | downward and upward |
| Power | 33 W |
| Luminous flux (source) | 4016 lm |
| Frequency | 50 - 60 Hz |
| CCT / Tonalità | 3000 K |
| Colour rendering index | 90 Ra |
| Safety class | 1 |
| IP | IP40 |
| Glow wire test | 650° |
| Operating temperature | 70 °C |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Driver included | Yes |
| Dimmable article | DALI |
| Emergency mode | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |

| Finishing casing | |
|------------------|-------------------------|
| Material | Iron |
| Colour | embossed white RAL 9003 |
| Processing | Coating |

| Finishing diffuser | |
|--------------------|---------|
| Material | PE |
| Colour | neutral |

| Finishing mounting frame | |
|--------------------------|-------------------------|
| Material | Iron |
| Colour | embossed white RAL 9003 |
| Processing | Coating |



Ceiling Lights | 220-240 V | topLED 33 W 700 mA | CRI 90
7653

Double emission ceiling lights for indoor application. The warm white LED light source with a diffused light distribution is composed of 168 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 4016 lm, with a 121.7 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of iron and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of pe; the mounting frame is made of iron, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of -- kg. The power supply driver is included in the delivery.

The total absorbed power is 33 W.

The device features protection class I and can be ceiling-mounted.

| Illuminotechnical Features | |
|---------------------------------------|----------------|
| Luminous flux (source) | 4016 lm |
| Colour temperature | 3000 K |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Colour rendering index | 90 Ra |