


Entourage_P1



Pendant Luminaires | 220-240 V | 5xE27
7669



Technical data	
Collection	ma[&]jde
Installation position	Ceiling
Installation environment	Indoor
Lamp cap	5 x E27 Max 46W
Frequency	50-60 Hz
Optic	Diffused
Light emission direction	downward
Safety class	1
IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Induzione	No
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing	
Material	PE
Colour	Beton dark grey
Processing	Coating

Finishing diffuser	
Material	PMMA
Colour	opaline
Processing	Satin finishing

Finishing mounting frame	
Material	Iron
Colour	embossed white RAL 9003
Processing	Coating



Pendant Luminaires | 220-240 V | 5xE27
7669

Single emission pendant luminaires for indoor application. Compatibility:
LED lamp, compact fluo 30 W, halogen 46 W; lamp cap 5xE27.

The device body is made of pe and features a beton dark grey finish, processed by means of coating; the diffuser is made of pmma with a satin finishing treatment; the mounting frame is made of iron, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 23.360 kg.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features

Colour temperature	2800 K
Colour rendering index	100 Ra
Luminous flux (source)	3500 lm