


Pendant Luminaires | 220-240 V | topLED 91 W 1550 mA | DALI | CRI 90  
7982



Technical data	
Collection	ma[&]de
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optic	Diffused
Light emission direction	upward
Power	91 W
Luminous flux (source)	9160 lm
Frequency	60 - 50 Hz
CCT / Tonalità	3000 K
Colour rendering index	90 Ra
Safety class	1
IP	IP20
Glow wire test	850°
Operating temperature	70 °C
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Dimmable article	DALI
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing	
Material	PU
Colour	white
Finishing diffuser	
Material	PC
Colour	transparent
Finishing mounting frame	
Material	Iron
Colour	embossed white RAL 9003
Processing	Coating

Pendand Luminaires | 220-240 V | topLED 91 W 1550 mA | DALI | CRI 90  
**7982**

Single emission pendand luminaires for indoor application. The warm white LED light source with a diffused light distribution is composed of 108 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 9160 lm, with a 100.7 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of pu and features a white finish; the diffuser is made of PC; the mounting frame is made of iron, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 7.8 kg. The power supply driver is included in the delivery.

The total absorbed power is 91 W.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features	
Luminous flux (source)	9160 lm
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra