




Pendant Luminaires | 220-240 V | topLED 55 W 1400 mA | DALI | CRI 90
7984



Technical data	
Collection	ma[&]de
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optic	Diffused
Light emission direction	upward
Power	55 W
Luminous flux (source)	5564 lm
Frequency	60 - 50 Hz
CCT / Tonalità	3000 K
Colour rendering index	90 Ra
Safety class	1
IP	IP20
Optical compartment IP	IP40
Glow wire test	850°
Operating temperature	70 °C
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Dimmable article	DALI
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing	
Material	PU
Colour	white
Finishing diffuser	
Material	PC - PMMA
Colour	transparent - white
Processing	Satin finishing
Finishing mounting frame	
Material	Iron
Colour	embossed white RAL 9003
Processing	Coating

Pendant Luminaires | 220-240 V | topLED 55 W 1400 mA | DALI | CRI 90
7984

Single emission pendant luminaires for indoor application. The warm white LED light source with a diffused light distribution is composed of 72 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 5564 lm, with a 101.2 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of pu and features a white finish; the diffuser is made of PC; the diffuser is made of pmma with a satin finishing treatment; the mounting frame is made of iron, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 3.745 kg. The power supply driver is included in the delivery.

The total absorbed power is 55 W.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features	
Luminous flux (source)	5564 lm
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra