








Pendant Luminares | 220-240 V | topLED 23 W 500 mA | DALI | CRI 90
8005N

 C.C.   



Technical data	
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	23 W
Luminous flux (source)	2914 lm
Frequency	50 - 60 Hz
CCT / Tonalità	4000 K
Colour rendering index	90 Ra
Safety class	1
IP	IP20
Optical compartment IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Driver included	Driver
Dimmable article	DALI
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Double emission
Net weight	2.220 Kg

Finishing diffuser	
Material	PE
Colour	neutral

Pendant Luminaires | 220-240 V | topLED 23 W 500 mA | DALI | CRI 90
8005N

Double emission pendant luminaires for indoor application. The warm white LED light source with a general lighting light distribution is composed of 104 topLEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 2914 lm, with a 126.7 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The diffuser is made of pe; the mounting frame is made of aluminium, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 2.220 kg.

The total absorbed power is 23 W.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features	
Luminous flux (source)	2914 lm
Colour temperature	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Life / Failure Ratio	
L80 B20 C0 80h	