


Ceiling Lights | 220-240 V | topLED 23 W 500 mA | DALI | CRI 90
8006N

   C.C.    



| Technical data | |
|--|------------------|
| Installation position | Ceiling |
| Installation environment | Indoor |
| Light Source | LED |
| Optics | General Lighting |
| Light emission direction | downward |
| Power | 23 W |
| Luminous flux (source) | 2914 lm |
| Frequency | 50 - 60 Hz |
| CCT / Tonalità | 4000 K |
| Colour rendering index | 90 Ra |
| Safety class | 1 |
| IP | IP40 |
| Glow wire test | 650° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Fire Rated (BS 476 PT21 compliant) | No |
| Driver included | Driver |
| Dimmable article | DALI |
| Induction | No |
| Emergency mode | No |
| Motion sensor | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| Type of light emission | Double emission |
| Net weight | 2.54 Kg |

| Finishing diffuser | |
|--------------------|---------|
| Material | PE |
| Colour | neutral |

Ceiling Lights | 220-240 V | topLED 23 W 500 mA | DALI | CRI 90
8006N

Double emission ceiling lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 104 topLED LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 2914 lm, with a 126.7 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The diffuser is made of pe; the mounting frame is made of aluminium, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 2.54 kg.

The total absorbed power is 23 W.

The device features protection class I and can be ceiling-mounted.

| Illuminotechnical Features | |
|---------------------------------------|----------------|
| Luminous flux (source) | 2914 lm |
| Colour temperature | 4000 K |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Colour rendering index | 90 Ra |
| Life / Failure Ratio | |
| L80 B20 C0 80h | |