


# Oxygen\_FL2



Floor Lamp | 220-240 V | topLED 36 W 1000 mA | CRI 90  
**8100**



Technical data	
Designer	Pio e Tito Toso
Installation position	Floor
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward and upward
Power	36 W
Luminous flux (source)	4042 lm
Frequency	60 - 50 Hz
CCT / Tonalità	3000 K
Colour rendering index	90 Ra
Safety class	1
IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Driver included	Driver
Dimmable article	PUSH DIM
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	4 m
Electric socket	Type F+E
Resin potting	No
Type of light emission	Double emission
Net weight	18.8 Kg

Finishing casing	
Material	PU
Colour	Azure/white

Finishing diffuser	
Material	PMMA
Colour	transparent
Processing	Laser engravings

Floor Lamp | 220-240 V | topLED 36 W 1000 mA | CRI 90  
8100

Double emission floor lamp for indoor application. The warm white LED light source with a general lighting light distribution is composed of 70 topLEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 4042 lm, with a 112.3 lm/W nominal luminous efficacy.

The device body is made of pu and features a azure/white finish; the diffuser is made of pmma with a laser engravings treatment; the mounting frame is made of iron, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 18.8 kg.

The total absorbed power is 36 W. The power supply cable is included and features.

The device features protection class I and can be floor-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	53 %
Luminous flux (source)	4042 lm
Luminaire luminous flux	2165 lm
Consumption	36 W
Luminaire efficacy	60 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Life / Failure Ratio	
L80 B20 C0 80000h	
UGR	
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20
UGR transversal	< 16
UGR axial	< 16
OPTICAL	
Light distribution simmetry	Symmetrical
Ottica C0/C180	138°

