Diphy_FL



Floor Lamp | 220-240 V | topLED 25 W 900 mA | CRI 90 8165













1962	
490	1933
	1933

Technical data	
Collection	ma[&]de
Installation position	Floor
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optic	Diffused
Light emission direction	downward and upward
Power	25 W
Luminous flux (source)	3743 lm
	60 - 50 Hz
CCT / Tonalità	3000 K
Colour rendering index	90 Ra
Safety class	1
IP	IP20
Optical compartment IP	IP40
Glow wire test	650°
Operating temperature	70 °C
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Dimmable article	Push Dim
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Electric socket	Type F+E
Resin potting	No

Finishing casing				
Material	Aluminium			
Colour	embossed white RAL 9003			
Processing	Coating			

Finishing diffuser			
Material	PMMA		
Colour	transparent		
Processing	Laser engravings		

Finishing mounting frame			
Material	Iron		
Colour	embossed white RAL 9003		
Processing	Coating		

Diphy_FL



Floor Lamp | 220-240 V | topLED 25 W 900 mA | CRI 90 **8165**

Double emission floor lamp for indoor application. The warm white LED light source with a diffused light distribution is composed of 200 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 3743 lm, with a 149.7 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of aluminium and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of pmma with a laser engravings treatment; the mounting frame is made of iron, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of kg. The power supply driver is included in the delivery.

The total absorbed power is 25 W. The power supply cable is included and features.

The device features protection class I and can be floor-mounted.

Illuminotechnical Features				
Luminous flux (source)	3743 lm			
Colour temperature	3000 K			
Standard Deviation of Colour Matching	3 Step MacAdam			
Colour rendering index	90 Ra			