


Halfpipe



Wall Lights | 220-240 V | topLED 9 W 500 mA | CRI 80
8391



| Technical data | |
|--|------------------|
| Installation position | Wall lights |
| Installation environment | Indoor |
| Light Source | LED |
| Optics | General Lighting |
| Light emission direction | downward |
| Power | 9 W |
| Luminous flux (source) | 1050 lm |
| Frequency | 60 - 50 Hz |
| CCT / Tonalità | 3000 K |
| Colour rendering index | 80 Ra |
| Safety class | 1 |
| IP | IP44 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Fire Rated (BS 476 PT21 compliant) | No |
| Driver included | Driver |
| Induction | No |
| Emergency mode | No |
| Motion sensor | No |
| Directional | Orientabile |
| total angle (horizontal plane) | 35 ° |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| Type of light emission | Single emission |

| Finishing diffuser | |
|--------------------|----------|
| Material | Silicone |
| Colour | opaline |



Wall Lights | 220-240 V | topLED 9 W 500 mA | CRI 80
8391

Single emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 30 topped LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 1050 lm, with a 116.7 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The diffuser is made of silicone; the mounting frame is made of aluminium, with a translucent finish. The ingress protection degree is IP44;

The total absorbed power is 9 W.

The device features protection class I and can be wall lights-mounted.

| Illuminotechnical Features | |
|---------------------------------------|----------------|
| Light Output Ratio (LOR) | 55 % |
| Luminous flux (source) | 1050 lm |
| Luminaire luminous flux | 582 lm |
| Consumption | 9 W |
| Luminaire efficacy | 64 lm/W |
| Colour temperature | 3000 K |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Colour rendering index | 80 Ra |
| Life / Failure Ratio | |
| L70 B20 C0 72.5h | |

| UGR | |
|-------------------|----------|
| X=4H Y=8H | S=0.25H |
| Reflection factor | 70/50/20 |
| UGR transversal | < 28 |
| UGR axial | < 16 |

| OPTICAL | |
|-----------------------------|--------------|
| Light distribution simmetry | Asymmetrical |
| Ottica C0/C180 | 112° |
| Ottica C90/C270 | 68° |

