





Uplights | 1 x powerLED 2,0 W 630 mA | CRI 80
86788W18



Technical data	
Type	Surface
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Optics	Radial
Power	2 W
Source lumens	233 lm
Current intensity	630mA
CCT / Tone	3000 K
Colour rendering index	80 Ra
C.C. / C.V.	CC
Energy class	A++
Safety class	3
IP	IP67
IK	IK10
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Operating temperature	-20°C / +50°C
Driver included	No
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	Yes
Drive-over	1000 Kg
Cable included	Yes
Cable length	3 m
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.4 Kg

Finishing casing

Material	Aluminium
Colour	grey
Processing	Coating

Finishing diffuser

Material	Glass
Colour	white
Processing	Sandblasting

Electronics



99179
On/Off Driver 180-300V AC



99186
On/Off Driver 180-300V AC



89420
On/Off Driver 190-250V AC / 260-360V DC

Uplights | 1 x powerLED 2,0 W 630 mA | CRI 80
86788W18

Single emission uplights for outdoor application. The warm white LED light source with a radial light distribution is composed of 1 powered LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 233 lm, with a 116.5 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a grey finish, processed by means of coating; the diffuser is made of glass with a sandblasting treatment. The ingress protection degree is IP67; the total weight is of 0.4 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 2,0 W. The power supply cable is included and features.

The device features protection class III and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Light Output Ratio (LOR)	89 %
Source lumens	233 lm
Delivered lumens	208 lm
Consumption	2,0 W
Luminaire efficacy	104 lm/W
Colour temperature	3000 K
Colour rendering index	80 Ra
LED Life / Failure Ratio	
L70 B10 C0 361980h (at Tj 60 °C Ta 25 °C)	

OPTICAL	
Light distribution simmetry	Symmetrical
C0/C180 optics	180°

