

BOX

17-Jun.-2016

2.0 | 3.0 LED

LED 8W | 220-240VAC | 50-60Hz | COB 2-step | incl. PS | phase-cut dim

CE IP20 0,3m 36°

2.0

200mm

white texture
aluminium brushed
copper
black texture

207164W_
207164L_
207164P_
207164B_

3.0

300mm

white texture
aluminium brushed
copper
black texture

207264W_
207264L_
207264P_
207264B_

LIGHT COLOUR

2700K | >80CRI | 480lm

2

3000K | >80CRI | 480lm

4

1800-2850K | >90CRI | 410lm

9

2.0 | 3.0 PAR16

max. 35W | GU10 | 220-240VAC | 50-60Hz

CE IP20 0,9m

2.0

200mm

white texture
aluminium brushed
copper
black texture

207120W0
207120L0
207120P0
207120B0

3.0


300mm

white texture
aluminium brushed
copper
black texture


207220W0
207220L0
207220P0
207220B0

OPTIONAL

for PAR16 lamps see our catalogue



DIMENSIONS




MOUNTING INSTRUCTION

- 1 Insert part A until it clicks in the lower part of the cover
- 2 Insert part B until it clicks in the higher part of the cover
- 3 POWER CONNECTION

Connect wiring to the power supply (for LED) or to terminal block (for PAR16)

PARALLEL CONNECTION



- 4 Mount the ceiling base on the ceiling
- 5 ONLY FOR PAR16
Insert the lamp



WEVER & DUCRÉ
LIGHTING

www.weverducre.com

Wever & Ducre bvba Kwadestraat 153 bus 2.1 8800 Roeselare

INSTALLATION
INSTRUCTIONS