





DEEP

CEILING RECESSED



1.0 LED

LED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.31kg IP20 0.3+D P 36°

76 90 4-30

	CODE
	112161W_
	112161S_
	112161B_

blade springs 78

	CODE
	112161W_C
	112161B_C

Light Colour Selection

	LUMEN	CRI	CODE
2700K	420-590	>90	3
3000K	470-640	>90	5
4000K	490-660	>90	6
1800-2850K	320-440	>95	9

ALWAYS USE

power supply

	CODE
350mA 10W	90223401
500mA 10W	90214404
500mA 15W dim	90224501

more power supplies on page 574

1.0 MR16

QR-CBC51 max.35W | GU5.3
12V | excl. power supply
aluminium powder coated

0.25kg IP20 0.9+D

76 90 4-30

	CODE
	112110W0
	112110S0
	112110B0

blade springs 78

	CODE
	112110W0C
	112110B0C

ALWAYS USE

power supply

	CODE
12V 10W dim	90221401
12V 25W dim	90221701
12V 70W dim	90221904

more specs on page 576

1.0 PAR16

PAR16 max.35W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.29kg IP20 0.9+D

76 105 4-30

	CODE
	112120W0
	112120S0
	112120B0

blade springs 78

	CODE
	112120W0C
	112120B0C

OPTIONAL

PAR16 LED GU10 7W
phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 577