





Article number 114440 Feed-in capability No COB LED Modul Lamp Number of light sources 1 Lamp included Yes Installation diameter 7 cm 7 cm Installation depth Height 6.2 cm Diameter 8.3 cm Net weight 0.319 kg Gross weight 0.385 kg 230 Volts Voltage 12 Watt Max. wattage Protection class **IP-rating** IP 65 Ream andle 38 Degree

Beam angle	38 Degree
Material	Aluminium / Glass
Colour	Matt black
Way of mounting	Recessed ceiling mounting
Average lifespan	40000 Hours
Colour temperature	3000 Kelvin
Colour rendering index	80
Luminous flux	630 lm
Energy class luminaire	A -
Light distribution type 1	direct
Light distribution type 3	rotationally symmetric

The innovative PATTA F-LED Downlight Set is suitable for ceiling thicknesses of up to 20 mm. Its IP65 class protection type means that it can be used outdoors and in high humidity spaces. The set is available in black, white, or brushed aluminum; and in round or square form. Equipped with a powerful, warm white COB LED in a pivotable mount, as well as an accompanying dimmable LED driver, the set can be used in any lighting situation. Connects to 230V electrical mains.

PATTA-I recessed ceiling light round, matt black, 9W, 38°, 3000K, incl. driver