





Article number	114451
Feed-in capability	No
Lamp	COB LED Modul
Number of light sources	1
Lamp included	Yes
Installation diameter	7 cm
Installation depth	7 cm
Length	8.3 cm
Width	8.3 cm
Height	6.2 cm
Net weight	0.337 kg
Gross weight	0.404 kg
Voltage	230 Volts
Max. wattage	12 Watt
Protection class	II
IP-rating	IP 65
Beam angle	38 Degree
Material	Aluminium / Glass
Colour	Matt white
Way of mounting	Recessed ceiling mounting
Average lifespan	40000 Hours
Colour temperature	3000 Kelvin
Colour rendering index	80
Luminous flux	765 lm
Energy class luminaire	A -
Light distribution type 1	direct
Light distribution type 3	rotationally symmetric

The innovative PATTA F-LED Downlight Set is suitable for ceiling thicknesses of up to 20 mm. Its IP65 class protection type means that it can be used outdoors and in high humidity spaces. The set is available in black, white, or brushed aluminum; and in round or square form. Equipped with a powerful, warm white COB LED in a pivotable mount, as well as an accompanying dimmable LED driver, the set can be used in any lighting situation. Connects to 230V electrical mains.

**PATTA-I recessed ceiling light** square, matt white, 9W, 38°, 3000K, incl. driver