



KADUX

recessed fitting, double-headed, QPAR51, rectangular, brushed aluminium, max. 100W, incl. clip springs

Article number	115526
Feed-in capability	No
LBS code	QPAR51
Lampholder / Socket	GU10
Number of light sources	2
Lamp included	No
Installation length	14 cm
Installation width	8 cm
Installation depth	13 cm
Length	15 cm
Width	9 cm
Height	13 cm
Net weight	0.584 kg
Gross weight	0.662 kg
Voltage	230 Volts
Max. wattage	100 Watt
Protection class	I
Energy efficiency class	A++
Lamp	GU10 230V
Material	Aluminium / Steel
Colour	Aluminium brushed
Way of mounting	Recessed ceiling mounting
Remark 1	Suitable for hollow ceilings with a max. thickness of 30 mm
Remark 2	The lamp heads can be rotated and swivelled
Light distribution type 1	direct

The recessed downlight ALU BOX is equipped with multi-directional lamp holders. Available with either one, two or three light outputs, the ALU BOX is designed for the use of GU10 halogen and LED lamps. The inner side of the housing is made from aluminium and painted black, giving the viewer an image of free-floating lamp heads. The aluminium-coloured frame completes the ALU BOX. The luminaire is ready for direct connection to 230V mains voltage. This luminaire is compatible with bulbs of the energy classes: E - A++