



STRETTA IP44 3400 K 057-063351EH

DATE	_____
PROJECT	_____
REMARK	_____
TYPE	_____
QUANTITY	_____

Quickinfo

GENERAL

Ceiling / Wall _____
Surface _____
anodised aluminum _____
2020 lm _____
2260 lm/m _____
IP44 _____

LED

3400 K _____
CRI \geq 80 _____
L90 / 50000 h _____
initial \leq 3 step MacAdam _____

OPTICAL

High Performance Opal _____

PHYSICAL

length 908 mm _____
width 77 mm _____
height 42 mm _____

ELECTRICAL

20 W _____
non DIM _____
99 lm/W _____
23 W/m _____



luminaire housing made of extruded aluminium profile; light tight final end caps; no visible screws; angular design; aluminium surface etched and plain anodised; end cover chrome plated; suitable for wall or ceiling mounting; light colour 3400 K; Binning \leq 3 step MacAdam; CRI \geq 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with three sided light beam; HPO (High Performance Opal) cover for uniform illumination; due to special material composition with increased transmission and diffusion; + 15% luminous efficiency compared to standard opal covers; protection rating IP44; PC I; incl. converter, non dimmable.

