

XAL TASK table

059-28115780

PROJECT

TYPE

NOTES

QUANTITY

DATE

GENERAL

Table
Standing
black
IP20
1030 lm
RAL9005 ^a
Extended Configuration

LED

3000 K
CRI ≥ 80
L80 / 50000 h
photobio. safety RG 0 - no Risk
initial ≤ 3 MacAdam

OPTICAL

Opal

PHYSICAL

length 227 mm
width 120 mm
height 880 mm
1.6 kg
tilt min -15°
tilt max 15°
rotation 360°

ELECTRICAL

touch DIM & movement sensor
11 W
94 lm/W
PC2 220-240V

^a RAL Palette colors may deviate slightly due to production conditions.



Desk lamp in puristic design, with rectangular lamp head with rounded edges in aluminium; extremely flat design (only 15mm); lamp head 360° rotatable and 15° tiltable; lamp arm with 3 joints for maximum flexibility; surface black powder coated; direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; opal PMMA cover; completely homogeneous illumination; light colour 3000 K; Binning initial ≤ 3 MacAdam; CRI ≥ 80; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; continuously adjustable dimming via optical sensor (10-100% analog); integrated USB charging socket for charging of a smart device; external power supply for converter with power plug; various mounting accessories can be used (accessory is listed separately);

Light Distribution

